

WATER TANK LEVEL SENSOR

Overview

NETOP Water Tank Level Threshold Sensor is a long range wireless sensor which can be used for detecting that Water Tank level is below or above from specific point. You can put the sensor into a water tank(let's say 5 meters higher from a base) and monitor whether the water level is up or down from the level which sensor states onto. So it can give information whether there is any water into the tank on this level or not. This sensor is compatible with LoRaWAN technology. The standard version of this sensor is powered by one replaceable 3.6 V AA sized battery (included with purchase).

Key Features

- Real plug & play
- Easy to mount & install
- Compatible with LoRaWAN™ specification
- Maintenance free – install & forget
- Secure communication
- Ultra Low Power Consumption
- Certifications: LoRaWAN™, CE



Communication Specs

- The sensor uses Low Power Wide Area Network-LPWAN technology(LoRa) for connectivity
- Compliant with AS923, AU915, EU868, KR920, IN865 or US915 MHz ISM bands
- Low power consumption
- Long range wireless data transmission(upto 15km)
- Antenna Types: Internal(default) or External(depend on request) Antenna
- Radio Performance : Upto +14 dBm TX power and -137 dBm RX sensitivity

Mechanics

- Housing: ABS
- Dimensions: 65 x 55 x 27 mm
- Operating temperature: -40°C to +85°C

Data Security

- AES-128

Power Supply

- AA Battery 3.6 V Li-SOCI2-Saft LS 14500 (Standard 1 piece)

Indicators

- RGB Status LED (on board)

Sensor Specifications

Output : 1 or 0
Data Transmission Period : Every water level changes

Certifications & Reliability

- LoRaWAN™ Certified
- CE
- EN 62479
- EN60950
- EN 301 489-1
- EN 301 489-17
- EN 300 328

Applications

- Water tank level applications